




Bearing No. 6014ZZ

r	1.1
d	70 mm
D	110 mm
B	20 mm
C	20 mm
Z_	14
B_	20
D_	110
fo	15.6
ra	1
C0	31
DI_	78.094
DE_	101.906
DA_	11.906
D_a	103.5
SRI	6.16
SRE	6.16
SRIX	0.025
SRIN	-0.025
Noun	Bearing
bomp	0
SREN	-0.025
SREX	0.025
Bore	2.756 Inch 70 Millimeter
mass	0.608
KBRG	6141
SBRG	10
yobi	6014ZZ
SDM_	90

Weight	0,608 Kg
LangID	1
r min.	1,1 mm
ALPHA_	0
UNSPSC	31171504
da min	76.5
C_conv	38000
da max	80,5 mm
da min.	76,5 mm
GRS rpm	6000
hidYobi	6014ZZ
ra max.	1 mm
Da max.	103,5 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Metal Shields
Size (mm)	70x110x20
Inventory	0.0
Snap Ring	No
Width (mm)	20
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	0.595
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6014ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.787 Inch 20 Millimeter

Outside Diameter	4.331 Inch 110 Millimeter
Long Description	70MM Bore; 110MM Outside Diameter; 20MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer Name	NSK
Weight / Kilogram	0.6
Internal Clearance	C0-Medium
Bore Diameter (mm)	70
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6014ZZ
Internal Special Features	No
(Grease) Lubrication Speed	6 000 r/min
Basic static load rating (C0)	31 kN
Basic dynamic load rating (C)	38 kN
Maximum Capacity / Filling Slot	No