




Bearing No. 6014ZZ

D	110 mm
d	70 mm
B	20 mm
C	20 mm
rn	0,5 mm
Noun	Bearing
Bore	2.756 Inch 70 Millimeter
UNSPSC	31171504
da max	80,5 mm
Weight	0,604 Kg
r min.	1,1 mm
da min.	76,5 mm
Da max.	103,5 mm
ra max.	1 mm
series:	60
Category	Single Row Ball Bearing
Size (mm)	70x110x20
Enclosure	2 Metal Shields
Inventory	0.0
Snap Ring	No
bore type:	Round
Width (mm)	20
Weight / LBS	1.347
maximum rpm:	7100 RPM
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove
Bearing number	6014ZZ
bore diameter:	70 mm
overall width:	20 mm
cage material:	Steel
fillet radius:	1.1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
Long Description	70MM Bore; 110MM Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.ntnamerica.com
bearing material:	High Carbon Chrome Steel
outside diameter:	110 mm
inner ring width:	20 mm
Manufacturer Name	NTN
Weight / Kilogram	0.611
outer ring width:	20 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	70
Internal Clearance	C0-Medium

snap ring included:	Without Snap Ring
Outer Diameter (mm)	110
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	31000 N
maximum rpm (grease):	6100 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	38000 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6014ZZ
Internal Special Features	No
manufacturer product page:	Click here
(Grease) Lubrication Speed	6 100 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	38 kN
Basic static load rating (C0)	31 kN
Maximum Capacity / Filling Slot	No