

**Bearing No. 23080-K-MB + AH3080G-H**

l	183 mm
e	0,24
D	600 mm
B	148 mm
a	10 mm
b	33 mm
m	143 kg / Weight
d	400 mm
Size (mm)	380x600x148
Width (mm)	148
d <sub>s</sub>	12,5 mm
C <sub>r</sub>	3050000 N / Dynamic load rating (radial)
n <sub>s</sub>	23,5 mm
D <sub>1</sub>	540,5 mm
Y <sub>1</sub>	2,79
Y <sub>2</sub>	4,15
Y <sub>0</sub>	2,73
n <sub>G</sub>	1120 1/min / Limiting speed
n <sub>B</sub>	680 1/min / Reference speed
m <sub>1</sub>	25,4 kg / Weight, withdrawal sleeve
C <sub>0r</sub>	6200000 N / Static load rating (radial)
Bearing number	23080-K-MB + AH3080G-H
d <sub>1H</sub>	380 mm
d <sub>2G</sub>	Tr420X5

$C_{ur}$	365000 N / Fatigue limit load, radial
$r_{min}$	5 mm
$r_{a\ max}$	4 mm
$d_{a\ min}$	418 mm
$D_{a\ max}$	582 mm
Bore Diameter (mm)	380
Outer Diameter (mm)	600
- AH3080G-H / Designation, withdrawal sleeve	AH3080GH / Designation, withdrawal sleeve