



Bearing No. 6015DDU

r	1.1
d	75 mm
D	115 mm
B	20 mm
C	20 mm
D_	115
C0	33.5
Z_	15
ra	1
fo	15.8
B_	20
DI_	83.094
SRI	6.16
SRE	6.16
DE_	106.906
DA_	11.906
D_a	108.5
KBRG	6161
SBRG	10
SRIN	-0.025
bomp	0
SREX	0.025
yobi	6015DDU
SRIX	0.025
mass	0.649
SDM_	95
SREN	-0.025
Bore	2.953 Inch 75 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	81.5
r min.	1,1 mm
Weight	0,649 Kg
ALPHA_	0
C_conv	39500
da max	85,5 mm
GRS rpm	3400
Da max.	108,5 mm
ra max.	1 mm
da min.	81,5 mm
hidYobi	6015DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	75x115x20
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	20
Prod_Type3	DGBB_SR_DD
Weight / LBS	1.431
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6015DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outer Race Width	0.787 Inch 20 Millimeter
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	4.528 Inch 115 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.645
Internal Clearance	C0-Medium
Bore Diameter (mm)	75
Outer Diameter (mm)	115
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6015DDU
Internal Special Features	No
(Grease) Lubrication Speed	3 400 r/min
Basic static load rating (C0)	33,5 kN
Basic dynamic load rating (C)	39,5 kN
Maximum Capacity / Filling Slot	No