



Bearing No. X32014XM/Y32014X

|                                 |                  |
|---------------------------------|------------------|
| R                               | 1,5 mm           |
| d                               | 70 mm            |
| D                               | 110 mm           |
| T                               | 25 mm            |
| B                               | 25 mm            |
| C                               | 19 mm            |
| r                               | 1,5 mm           |
| Da                              | 105 mm           |
| Ab                              | 1,8 mm           |
| Aa                              | 2,4 mm           |
| Db                              | 100 mm           |
| da                              | 76 mm            |
| db                              | 78 mm            |
| a -                             | 1 mm             |
| Weight                          | 0,87 Kg          |
| Size (mm)                       | 70x110x25        |
| Width (mm)                      | 25               |
| Factor (K)                      | 1,34             |
| Factor (G1)                     | 74,1             |
| Factor (Cg)                     | 0,0586           |
| Factor (G2)                     | 44,8             |
| Bearing number                  | X32014XM/Y32014X |
| Bore Diameter (mm)              | 70               |
| Outer Diameter (mm)             | 110              |
| Calculation factor (e)          | 0,43             |
| Basic static load rating (C0)   | 163 kN           |
| Basic dynamic load rating (C1)  | 93,8 kN          |
| Basic dynamic load rating (C90) | 24,3             |



|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 18,1 |
|----------------------------------|------|