




Bearing No. 6015VV

D	115 mm
d	75 mm
B	20 mm
C	20 mm
r	1.1
Z_	15
B_	20
D_	115
ra	1
C0	33.5
fo	15.8
DI_	83.094
SRI	6.16
D_a	108.5
DE_	106.906
DA_	11.906
SRE	6.16
SRIN	-0.025
SBRG	10
yobi	6015VV
SDM_	95
SREX	0.025
KBRG	6151
bomp	0
mass	0.649
Bore	2.953 Inch 75 Millimeter
SRIX	0.025
SREN	-0.025
Noun	Bearing

ALPHA_	0
da min	81.5
LangID	1
r min.	1,1 mm
UNSPSC	31171504
C_conv	39500
da max	85,5 mm
Weight	0,649 Kg
hidYobi	6015VV
Da max.	108,5 mm
da min.	81,5 mm
ra max.	1 mm
GRS rpm	5600
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	75x115x20
Width (mm)	20
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.64
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6015VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.787 Inch 20 Millimeter
Outside Diameter	4.528 Inch 115

	Millimeter
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.65
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	75
Outer Diameter (mm)	115
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6015VV
Internal Special Features	No
(Grease) Lubrication Speed	5 600 r/min
Basic static load rating (C0)	33,5 kN
Basic dynamic load rating (C)	39,5 kN
Maximum Capacity / Filling Slot	No