




Bearing No. 7008 ACE/HCP4AL

b	1.7 mm
d	40 mm
a	20.3 mm
B	15 mm
D	68 mm
Ball - z	19
Size (mm)	68x40x15
Width (mm)	15
Mass bearing	0.17 kg
d ₂	47.6 mm
D ₁	58.25 mm
d _n	51.6 mm
C ₁	7.8 mm
C ₂	2.5 mm
C ₃	3 mm
C ₂	2.5 mm
C ₁	7.8 mm
d _n	51.6 mm
D ₁	58.25 mm
d ₂	47.6 mm
d ₁	49.7 mm
d ₁	49.7 mm
C ₃	3 mm
Bearing number	7008 ACE/HCP4AL
Preload class A	96 N/micron
Preload class B	143 N/micron
G _{ref}	2.8 cm3
Preload class C	187 N/micron
Number of balls z	19

Bore Diameter (mm)	68
r_b max.	0.6 mm
r_a max.	1 mm
D_b max.	63.8 mm
D_a max.	63.4 mm
d_a min.	44.6 mm
d_b min.	44.6 mm
Outer Diameter (mm)	40
r_b - max.	0.6 mm
$r_{3,4}$ min.	0.6 mm
d_b - min.	44.6 mm
D_a - max.	63.4 mm
D_b - max.	63.8 mm
$r_{1,2}$ min.	1 mm
d_a - min.	44.6 mm
r_a - max.	1 mm
Ball - D_w	7.144 mm
Calculation factor f	1.06
Calculation factor e	0.68
$r_{3,4}$ - min.	0.6 mm
Calculation factor - f	1.06
$r_{1,2}$ - min.	1 mm
Calculation factor - e	0.68
Ball diameter D_w	7.144 mm
Basic dynamic load rating C	11.7 kN
Preload class C G_C	630 N
Basic dynamic load rating - C	11.7 kN
Preload class B G_B	310 N
Preload class A G_A	105 N
Preload class C - G_C	630 N

Preload class A - G_A	105 N
Preload class B - G_B	310 N
Calculation factor f_1	0.99
Fatigue load limit P_u	0.305 kN
Calculation factor f_{HC}	1.01
Calculation factor f_{2C}	1.06
Calculation factor f_{2B}	1.03
Calculation factor f_{2A}	1
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Limiting speed for oil lubrication	50000 mm/min
Calculation factor - Y_1	0.92
Fatigue load limit - P_u	0.305 kN
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{HC}	1.01
Calculation factor - f_{2C}	1.06
Calculation factor - f_{2B}	1.03
Limiting speed for grease lubrication	32000 r/min
Basic static load rating C_0	7.2 kN
Static axial stiffness, preload class A	96 N/ μ m
Static axial stiffness, preload class C	187 N/ μ m
Static axial stiffness, preload class B	143 N/ μ m
Attainable speed for grease lubrication	32000 r/min

Basic static load rating - C_0	7.2 kN
Attainable speed for oil-air lubrication	50000 r/min
Reference grease quantity G_{ref}	2.8 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67