



Bearing No. 7008DF

D	68 mm
d	40 mm
B	15 mm
a	23 mm
2B	30 mm
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
Width	1.181 Inch 30 Millimeter
UNSPSC	31171531
Weight	0,444 Kg
r min.	1 mm
db min	45,5 mm
ra max.	1 mm
Da max.	62,5 mm
r1 min.	0,6 mm
ra1 max.	0,6 mm
Category	Angular Contact Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	40x68x15
Enclosure	Open
Width (mm)	15
Flush Ground	Yes
Inch - Metric	Metric
Contact Angle	30 Degree
Cage Material	Steel
Product Group	B00308
Keyword String	Angular Contact

Bearing number	7008DF
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Angle (?)	25 °
Long Description	40MM Bore; 68MM Outside Diameter; 30MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 30 Degree; 2 (1 Pair); D
Outside Diameter	2.677 Inch 68 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0.424
Manufacturer Name	NTN
Internal Clearance	C0-Medium
Number of Bearings	2 (1 Pair)
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Mounting Arrangement	Duplex-Face to Face
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
Manufacturer Item Number	7008DF
(Grease) Lubrication Speed	8 300 r/min
Basic dynamic load rating (C)	30,5 kN
Basic static load rating (C0)	29,2 kN
Maximum Capacity /	No

Filling Slot	
--------------	--