



Bearing No. 6017DDU

r	1.1
d	85 mm
D	130 mm
B	22 mm
C	22 mm
D_	130
C0	43
Z_	15
ra	1
fo	15.8
B_	22
DI_	94.006
SRI	6.98
SRE	6.98
DE_	120.994
DA_	13.494
D_a	123.5
KBRG	6161
SBRG	10
SRIN	-0.025
bomp	0
SREX	0.025
yobi	6017DDU
SRIX	0.025
Bore	3.346 Inch 85 Millimeter
SDM_	107.5
SREN	-0.025
mass	0.918
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	91.5
r min.	1,1 mm
Weight	0,918 Kg
ALPHA_	0
C_conv	49500
da max	96 mm
GRS rpm	3000
Da max.	123,5 mm
ra max.	1 mm
da min.	91,5 mm
hidYobi	6017DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	85x130x22
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	22
Prod_Type3	DGBB_SR_DD
Weight / LBS	2.0242
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6017DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	5.118 Inch 130

	Millimeter
Outer Race Width	0.866 Inch 22 Millimeter
Long Description	85MM Bore; 130MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.92
Internal Clearance	C0-Medium
Bore Diameter (mm)	85
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6017DDU
Internal Special Features	No
(Grease) Lubrication Speed	3 000 r/min
Basic static load rating (C0)	43 kN
Basic dynamic load rating (C)	49,5 kN
Maximum Capacity / Filling Slot	No