



Bearing No. HS7008-C-T-P4S

|                     |                                                                   |
|---------------------|-------------------------------------------------------------------|
| D                   | 68 mm                                                             |
| d                   | 40 mm                                                             |
| B                   | 15 mm                                                             |
| a                   | 15 mm                                                             |
| m                   | 0,211 kg / Weight                                                 |
| ?                   | 15 ° / Angle                                                      |
| Size (mm)           | 40x68x15                                                          |
| Width (mm)          | 15                                                                |
| D <sub>a</sub>      | 58,5 mm / Tolerance: H12                                          |
| C <sub>r</sub>      | 9400 N / Dynamic load rating (radial)                             |
| d <sub>a</sub>      | 49 mm / Tolerance: h12                                            |
| C <sub>0r</sub>     | 5700 N / Static load rating (radial)                              |
| Bearing number      | HS7008-C-T-P4S                                                    |
| r <sub>min</sub>    | 1 mm                                                              |
| n <sub>G Ol</sub>   | 45000 1/min / Limiting speed for minimal quantity oil lubrication |
| r <sub>a max</sub>  | 1 mm                                                              |
| Bore Diameter (mm)  | 40                                                                |
| n <sub>G Fett</sub> | 30000 1/min / Limiting speed for grease lubrication               |
| Outer Diameter (mm) | 68                                                                |