



Bearing No. 7010 ACE/HCP4AH1

K	0.5 mm
a	23.3 mm
d	50 mm
D	80 mm
B	16 mm
Ball - z	21
Size (mm)	80x50x16
Width (mm)	16
Mass bearing	0.23 kg
d _n	62.3 mm
D ₁	69.75 mm
d ₁	60.25 mm
C ₁	5.32 mm
D ₁	69.75 mm
d ₂	57.9 mm
C ₁	5.32 mm
d ₁	60.25 mm
d _n	62.3 mm
d ₂	57.9 mm
Bearing number	7010 ACE/HCP4AH1
Preload class A	115 N/micron
Preload class B	173 N/micron
Preload class C	227 N/micron
G _{ref}	4.1 cm ³
Number of balls z	21
Bore Diameter (mm)	80
r _b max.	0.6 mm
r _a max.	1 mm
D _b max.	75.8 mm

D _a max.	75.4 mm
d _a min.	54.6 mm
d _b min.	54.6 mm
Outer Diameter (mm)	50
r _a - max.	1 mm
r _{3,4} min.	0.6 mm
D _a - max.	75.4 mm
d _b - min.	54.6 mm
r _{1,2} min.	1 mm
Ball - D _w	7.938 mm
r _b - max.	0.6 mm
D _b - max.	75.8 mm
Calculation factor f	1.08
Calculation factor e	0.68
d _a - min.	54.6 mm
Calculation factor - f	1.08
r _{3,4} - min.	0.6 mm
r _{1,2} - min.	1 mm
Calculation factor - e	0.68
Ball diameter D _w	7.938 mm
Basic dynamic load rating C	14.8 kN
Preload class A G _A	130 N
Preload class B G _B	400 N
Preload class C G _C	800 N
Basic dynamic load rating - C	14.8 kN
Preload class B - G _B	400 N
Preload class C - G _C	800 N
Preload class A - G _A	130 N
Fatigue load limit P _u	0.425 kN
Calculation factor f ₁	0.99

Calculation factor f_{2C}	1.06
Calculation factor f_{2B}	1.03
Calculation factor f_{HC}	1.01
Calculation factor f_{2A}	1
Calculation factor - f_1	0.99
Limiting speed for oil lubrication	41000 mm/min
Fatigue load limit - P_u	0.425 kN
Calculation factor - Y_0	0.76
Calculation factor - Y_1	0.92
Calculation factor - X_2	0.67
Calculation factor - Y_2	1.41
Calculation factor - f_{HC}	1.01
Calculation factor - f_{2C}	1.06
Calculation factor - f_{2B}	1.03
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	27000 r/min
Basic static load rating C_0	10 kN
Static axial stiffness, preload class C	227 N/ μ m
Attainable speed for grease lubrication	27000 r/min
Static axial stiffness, preload class B	173 N/ μ m
Static axial stiffness, preload class A	115 N/ μ m
Attainable speed for oil-air lubrication	41000 r/min
Basic static load rating - C_0	10 kN
Reference grease	4.1 cm ³

quantity G_{ref}	
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67