



Bearing No. 6019DDU

r	1.5
d	95 mm
D	145 mm
B	24 mm
C	24 mm
D_	145
C0	54
Z_	15
ra	1.5
fo	15.8
B_	24
DI_	106.419
SRI	7.8
SRE	7.8
DE_	136.581
DA_	15.081
D_a	137
KBRG	6161
SBRG	10
SRIN	-0.03
bomp	0
SREX	0.03
yobi	6019DDU
SRIX	0.03
Bore	3.74 Inch 95 Millimeter
SDM_	121.5
SREN	-0.03
mass	1.23
Noun	Bearing
LangID	1

UNSPSC	31171504
da min	103
ALPHA_	0
r min.	1,5 mm
Weight	1,23 Kg
C_conv	60500
da max	108,5 mm
Da max.	137 mm
ra max.	1,5 mm
GRS rpm	2600
da min.	103 mm
hidYobi	6019DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	95x145x24
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	24
Prod_Type3	DGBB_SR_DD
Weight / LBS	2.7122
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6019DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.945 Inch 24 Millimeter

Outside Diameter	5.709 Inch 145 Millimeter
Long Description	95MM Bore; 145MM Outside Diameter; 24MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	1.2
Internal Clearance	C0-Medium
Bore Diameter (mm)	95
Outer Diameter (mm)	145
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6019DDU
Internal Special Features	No
(Grease) Lubrication Speed	2 600 r/min
Basic static load rating (C0)	54 kN
Basic dynamic load rating (C)	60,5 kN
Maximum Capacity / Filling Slot	No