



Bearing No. 6020DDU

r	1.5
d	100 mm
D	150 mm
B	24 mm
C	24 mm
D_	150
C0	54
Z_	15
ra	1.5
fo	15.9
B_	24
DI_	109.919
SRI	7.8
SRE	7.8
DE_	140.081
DA_	15.081
D_a	142
KBRG	6161
SBRG	10
SRIN	-0.03
bomp	0
SREX	0.03
yobi	6020DDU
SRIX	0.03
Bore	3.937 Inch 100 Millimeter
SDM_	125
SREN	-0.03
mass	1.29
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	108
ALPHA_	0
r min.	1,5 mm
Weight	1,29 Kg
C_conv	60000
da max	112,5 mm
Da max.	142 mm
ra max.	1,5 mm
GRS rpm	2600
da min.	108 mm
hidYobi	6020DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	100x150x24
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	24
Prod_Type3	DGBB_SR_DD
Weight / LBS	2.8445
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6020DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	5.906 Inch 150 Millimeter
Long Description	100MM Bore; 150MM Outside Diameter; 24MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.945 Inch 24 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	1.27
Internal Clearance	C0-Medium
Bore Diameter (mm)	100
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6020DDU
Internal Special Features	No
(Grease) Lubrication Speed	2 600 r/min
Basic static load rating (C0)	54 kN
Basic dynamic load rating (C)	60 kN
Maximum Capacity / Filling Slot	No