



Bearing No. 32006JR

D	55 mm
d	30 mm
T	17 mm
B	17 mm
C	13 mm
a	13,6 mm
e	0.43
Cr	47.9
Cu	6.75
Y0	0.77
Y1	1.39
C0r	48.0
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
a(mm)	13.6
Da min	47 mm
da max	35 mm
Weight	0,177 Kg
r min.	1 mm
r(min)	1
UNSPSC	31171516
Db(min)	52
db(max)	35
Da(max)	49.5
Da(min)	47
r1(min)	1
Sa(min)	3
Sb(min)	4
ra(max)	1

rb(max)	1
da(min)	35.5
ra max.	1 mm
Db min.	52 mm
Da max.	49,5 mm
da min.	35,5 mm
r2 min.	1 mm
rb max.	1 mm
Oil lub.	9400
Category	Tapered Roller Bearings Assembly
Size (mm)	30x55x17
Component	Assembly
Inventory	0.0
Width (mm)	17
Grease lub.	7000
Bearing No.	32006JR
Basic Number	32006
Weight / LBS	0.39
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	0.669 Inch 17 Millimeter
Bearing number	32006JR
Precision Class	Standard
(Refer.)Mass(kg)	0.177
Outside Diameter	2.165 Inch 55 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 30MM Bore; 55MM Outside

	Diameter; 17MM Assembly Width; Single Row of Rollers
Weight / Kilogram	0.18
Manufacturer Name	KOYO
Bore Diameter (mm)	30
Outer Diameter (mm)	55
Minimum Buy Quantity	N/A
Calculation factor (e)	0,43
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	9400 r/min
Calculation factor (Y0)	0,77
Manufacturer Item Number	32006JR
(Grease) Lubrication Speed	7000 r/min
Basic static load rating (C0)	48 kN
Basic dynamic load rating (C)	38,2 kN