



Bearing No. 6021

r	2
d	105 mm
D	160 mm
B	26 mm
C	26 mm
ra	2
C0	66
fo	15.8
B_	26
D_	160
Z_	15
DI_	117.831
D_a	151
DE_	151.169
DA_	16.669
SRE	8.63
SRI	8.63
SDM_	134.5
SREN	-0.03
mass	1.58
Bore	4.134 Inch 105 Millimeter
SBRG	10
SRIX	0.03
KBRG	6101
Noun	Bearing
SRIN	-0.03
bomp	0
SREX	0.03
yobi	6021

UNSPSC	31171504
C_conv	72500
Weight	1,58 Kg
da max	120 mm
LangID	1
da min	114
r min.	2 mm
ALPHA_	0
ra max.	2 mm
Oil rpm	4800
Da max.	151 mm
hidYobi	6021
GRS rpm	4000
series:	60
da min.	114 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	105x160x26
Enclosure	Open
Inventory	0.0
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	26
Weight / LBS	1.58
maximum rpm:	4800 RPM
Inch - Metric	Metric
Cage Material	Steel
closure type:	Open
Product Group	B00308
Bearing number	6021
bore diameter:	105 mm

fillet radius:	2 mm
Keyword String	Ball
cage material:	Steel
overall width:	26 mm
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	105MM Bore; 160MM Outside Diameter; 26MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	6.299 Inch 160 Millimeter
Outer Race Width	1.024 Inch 26 Millimeter
Weight / Kilogram	1.645
precision rating:	ABEC 1 (ISO Class Normal)
outer ring width:	26 mm
Manufacturer Name	NSK
outside diameter:	160 mm
Bore Diameter (mm)	105
Internal Clearance	C0-Medium
Outer Diameter (mm)	160
internal clearance:	C0
Minimum Buy Quantity	N/A
static load capacity:	66000 N
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	72500 N

(Oil) Lubrication Speed	4 800 r/min
Manufacturer Item Number	6021
Internal Special Features	No
(Grease) Lubrication Speed	4 000 r/min
operating temperature range:	Maximum of +250 °F
Basic static load rating (C0)	66 kN
Basic dynamic load rating (C)	72,5 kN
Maximum Capacity / Filling Slot	No