



Bearing No. 32008JR

D	68 mm
d	40 mm
T	19 mm
B	19 mm
C	14,5 mm
a	15,1 mm
e	0.38
Cr	67.2
Cu	10.3
Y0	0.87
Y1	1.58
C0r	71.4
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
a(mm)	15.1
Da min	60 mm
da max	46 mm
Weight	0,282 Kg
r min.	1 mm
r(min)	1
UNSPSC	31171516
Db(min)	65
db(max)	46
Da(max)	62.5
Da(min)	60
r1(min)	1
Sa(min)	4
Sb(min)	4.5
ra(max)	1

rb(max)	1
da(min)	45.5
ra max.	1 mm
Db min.	65 mm
Da max.	62,5 mm
da min.	45,5 mm
r2 min.	1 mm
rb max.	1 mm
Oil lub.	7400
Category	Tapered Roller Bearings Assembly
Size (mm)	40x68x19
Component	Assembly
Inventory	0.0
Width (mm)	19
Grease lub.	5600
Bearing No.	32008JR
Basic Number	32008
Weight / LBS	0.622
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	0.748 Inch 19 Millimeter
Bearing number	32008JR
Precision Class	Standard
(Refer.)Mass(kg)	0.282
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 40MM Bore; 68MM Outside Diameter; 19MM Assembly Width; Single

	Row of Rollers
Outside Diameter	2.677 Inch 68 Millimeter
Weight / Kilogram	0.28
Manufacturer Name	KOYO
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,38
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	7400 r/min
Calculation factor (Y0)	0,87
Manufacturer Item Number	32008JR
(Grease) Lubrication Speed	5600 r/min
Basic static load rating (C0)	71,4 kN
Basic dynamic load rating (C)	53,5 kN