



Bearing No. 6021N

D	160 mm
d	105 mm
B	26 mm
C	26 mm
a	3.71 mm
b	3.1 mm
r1	0.5 mm
D1	155.22 mm
Width	26 mm
Weight	1.54 Kg
r min.	2 mm
r1 min.	0.5 mm
a (max)	3.7 mm
da (min)	113 mm
Cy (max)	6.1 mm
Da (max)	152 mm
Dx (min)	172 mm
ra (max)	2 mm
Factor fo	15.8
Bore Type	Cylindrical Bore
Enclosure	Open
Size (mm)	105x160x26
Bore Size	105 mm
Width (mm)	26
Groove Width	3.1 mm
Configuration	Single Row
Bearing number	6021N
Groove Diameter	155.2 mm
Outside Diameter	160 mm
Radial Clearance	0.015 to 0.041 mm

Static Load Rating	65,500 N
Bore Diameter (mm)	105
Dynamic Load Rating	72,500 N
Outer Diameter (mm)	160
Limiting Speed - Oil	4,800 rpm
Fillet Radius/Chamfer	2 mm
Limiting Speed - Grease	4,000 rpm
(Grease) Lubrication Speed	4000 r/min
Basic static load rating (C0)	65,5 kN
Basic dynamic load rating (C)	72,5 kN