



Bearing No. H715345/H715311

e	0.47
d	71,438 mm
D	136,525 mm
T	46,038 mm
B	46,038 mm
C	36,512 mm
a	37,1 mm
Da	119 mm
B_	46.038
Db	132 mm
da	92 mm
Y0	0.7
db	84 mm
C0	370
D_	136.525
Z_	22
C_	36.512
Y1	1.3
DE_	119.5
SLR	35.6
D_a	119
DI_	93.834
DA1	14.481
DA2	12.107
CUP	0.961
DA_	13.299
D_b	132
RAr	216.5
SDM_	106.757
KBRG	3161

yobi	H715345/H715311
CONE	2.15
ALP21	35
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	50
r min.	3,5 mm
LangID	1
Weight	3,111 Kg
ALPHA_	17.5
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	3400
outer r	3.3
hidYobi	H715345/H715311
GRS rpm	2600
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	71.438x136.525x46.038
SHOG_yobi	H715345/H715311
Prod_Type3	TRBSR_ID_A
Width (mm)	46,038
Bearing number	H715345/H715311
Bore Diameter (mm)	71,438
Outer Diameter (mm)	136,525
Calculation factor (e)	0,47

(Oil) Lubrication Speed	3400 r/min
Calculation factor (Y0)	0,7
(Grease) Lubrication Speed	2600 r/min
Basic static load rating (C0)	370 kN
Basic dynamic load rating (C)	233 kN