



Bearing No. 32014JR

D	110 mm
d	70 mm
T	25 mm
B	25 mm
C	19 mm
a	23,6 mm
e	0.43
Cr	136
Cu	24.8
Y0	0.76
Y1	1.38
C0r	163
Bore	2.756 Inch 70 Millimeter
Noun	Bearing
a(mm)	23.6
Da min	98 mm
da max	78 mm
Weight	0,884 Kg
r min.	1,5 mm
r(min)	1.5
UNSPSC	31171516
Db(min)	105
db(max)	78
Da(max)	101.5
Da(min)	98
r1(min)	1.5
Sa(min)	5
Sb(min)	6
ra(max)	1.5

rb(max)	1.5
da(min)	78.5
ra max.	1,5 mm
Db min.	105 mm
Da max.	101,5 mm
da min.	78,5 mm
r2 min.	1,5 mm
rb max.	1,5 mm
Oil lub.	4400
Category	Tapered Roller Bearings Assembly
Size (mm)	70x110x25
Component	Assembly
Inventory	0.0
Width (mm)	25
Grease lub.	3300
Bearing No.	32014JR
Basic Number	32014
Weight / LBS	1.949
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	0.984 Inch 25 Millimeter
Bearing number	32014JR
Precision Class	Standard
(Refer.)Mass(kg)	0.884
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 70MM Bore; 110MM Outside Diameter; 25MM Assembly Width; Single

	Row of Rollers
Outside Diameter	4.331 Inch 110 Millimeter
Weight / Kilogram	0.89
Manufacturer Name	KOYO
Bore Diameter (mm)	70
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,43
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	4400 r/min
Calculation factor (Y0)	0,76
Manufacturer Item Number	32014JR
(Grease) Lubrication Speed	3300 r/min
Basic static load rating (C0)	163 kN
Basic dynamic load rating (C)	108 kN