




Bearing No. 7013 ACD/HCP4AL

b	1.9 mm
d	65 mm
a	28.3 mm
B	18 mm
D	100 mm
Ball - z	20
Size (mm)	100x65x18
Width (mm)	18
Mass bearing	0.36 kg
d ₂	75.8 mm
D ₁	89.2 mm
d _n	78.1 mm
C ₁	9.7 mm
C ₂	4.3 mm
C ₃	3.8 mm
C ₂	4.3 mm
C ₁	9.7 mm
d _n	78.1 mm
D ₁	89.2 mm
d ₂	75.8 mm
d ₁	75.8 mm
d ₁	75.8 mm
C ₃	3.8 mm
Bearing number	7013 ACD/HCP4AL
Preload class B	253 N/micron
Preload class A	193 N/micron
G _{ref}	5.7 cm3
Preload class D	453 N/micron
Preload class C	335 N/micron

Number of balls z	20
Bore Diameter (mm)	100
r_b max.	0.6 mm
r_a max.	1 mm
D_b max.	96.8 mm
D_a max.	94 mm
d_a min.	71 mm
d_b min.	71 mm
Outer Diameter (mm)	65
r_b - max.	0.6 mm
d_b - min.	71 mm
d_a - min.	71 mm
D_b - max.	96.8 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
D_a - max.	94 mm
r_a - max.	1 mm
Ball - D_w	11.112 mm
Calculation factor f	1.13
Calculation factor e	0.68
Calculation factor - f	1.13
$r_{1,2}$ - min.	1.1 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - e	0.68
Ball diameter D_w	11.112 mm
Basic dynamic load rating C	39 kN
Preload class A G_A	240 N
Preload class B G_B	480 N
Preload class C G_C	960 N
Basic dynamic load rating - C	39 kN
Preload class D G_D	1920 N

Preload class C - G_C	960 N
Preload class B - G_B	480 N
Preload class A - G_A	240 N
Preload class D - G_D	1920 N
Fatigue load limit P_u	1.5 kN
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1.02
Calculation factor - Y_0	0.76
Calculation factor - Y_2	1.41
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - X_2	0.67
Fatigue load limit - P_u	1.5 kN
Limiting speed for oil lubrication	22000 mm/min
Calculation factor - f_{2B}	1.02
Calculation factor - f_{HC}	1.02
Calculation factor - f_{2D}	1.08
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	15000 r/min
Basic static load rating C_0	35.5 kN
Static axial stiffness, preload class A	193 N/ μ m
Static axial stiffness,	453 N/ μ m

preload class D	
Static axial stiffness, preload class C	335 N/μm
Static axial stiffness, preload class B	253 N/μm
Attainable speed for grease lubrication	15000 r/min
Attainable speed for oil- air lubrication	22000 r/min
Basic static load rating - C_0	35.5 kN
Reference grease quantity G_{ref}	5.7 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back- to-back, face-to-face) Y_1	0.92
Calculation factor (back- to-back, face-to-face) Y_2	1.41
Calculation factor (back- to-back, face-to-face) Y_0	0.76
Calculation factor (back- to-back, face-to-face) X_2	0.67