



Bearing No. 32017JR

D	130 mm
d	85 mm
T	29 mm
B	29 mm
C	22 mm
a	28 mm
e	0.44
Cr	189
Cu	35.5
Y0	0.75
Y1	1.36
C0r	234
Bore	3.346 Inch 85 Millimeter
Noun	Bearing
a(mm)	28.0
Da min	117 mm
da max	94 mm
Weight	1,38 Kg
r min.	1,5 mm
r(min)	1.5
UNSPSC	31171516
Db(min)	125
db(max)	94
Da(max)	121.5
Da(min)	117
r1(min)	1.5
Sa(min)	6
Sb(min)	7
ra(max)	1.5

rb(max)	1.5
da(min)	93.5
ra max.	1,5 mm
Db min.	125 mm
Da max.	121,5 mm
da min.	93,5 mm
r2 min.	1,5 mm
rb max.	1,5 mm
Oil lub.	3700
Category	Tapered Roller Bearings Assembly
Size (mm)	85x130x29
Component	Assembly
Inventory	0.0
Width (mm)	29
Grease lub.	2800
Bearing No.	32017JR
Basic Number	32017
Weight / LBS	3.042
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	1.142 Inch 29 Millimeter
Bearing number	32017JR
Precision Class	Standard
(Refer.)Mass(kg)	1.38
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 85MM Bore; 130MM Outside Diameter; 29MM Assembly Width; Single

	Row of Rollers
Outside Diameter	5.118 Inch 130 Millimeter
Weight / Kilogram	1.49
Manufacturer Name	KOYO
Bore Diameter (mm)	85
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,44
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	3700 r/min
Calculation factor (Y0)	0,75
Manufacturer Item Number	32017JR
(Grease) Lubrication Speed	2800 r/min
Basic static load rating (C0)	234 kN
Basic dynamic load rating (C)	150 kN