



Bearing No. 6026

r	2
d	130 mm
D	200 mm
B	33 mm
C	33 mm
ra	2
C0	101
fo	15.8
B_	33
D_	200
Z_	15
DI_	144.362
D_a	191
DE_	185.638
DA_	20.638
SRE	10.68
SRI	10.68
SDM_	165
SREN	-0.04
mass	3.26
Bore	5.118 Inch 130 Millimeter
SBRG	10
SRIX	0.04
KBRG	6101
Noun	Bearing
SRIN	-0.04
bomp	0
SREX	0.04
yobi	6026

UNSPSC	31171504
C_conv	106000
Weight	3,26 Kg
da max	148,5 mm
LangID	1
da min	139
r min.	2 mm
ALPHA_	0
ra max.	2 mm
Oil rpm	3600
Da max.	191 mm
hidYobi	6026
GRS rpm	3000
series:	60
da min.	139 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	130x200x33
Enclosure	Open
Inventory	0.0
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	33
Weight / LBS	3.15
maximum rpm:	3600 RPM
Inch - Metric	Metric
Cage Material	Steel
closure type:	Open
Product Group	B00308
Bearing number	6026
bore diameter:	130 mm

fillet radius:	2 mm
Keyword String	Ball
cage material:	Steel
overall width:	33 mm
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.299 Inch 33 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
Weight / Kilogram	3.15
precision rating:	ABEC 1 (ISO Class Normal)
outer ring width:	33 mm
Manufacturer Name	NSK
outside diameter:	200 mm
Bore Diameter (mm)	130
Internal Clearance	C0-Medium
Outer Diameter (mm)	200
internal clearance:	C3
Minimum Buy Quantity	N/A
static load capacity:	101000 N
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	106000 N

(Oil) Lubrication Speed	3 600 r/min
Manufacturer Item Number	6026
Internal Special Features	No
(Grease) Lubrication Speed	3 000 r/min
operating temperature range:	Maximum of +250 °F
Basic static load rating (C0)	101 kN
Basic dynamic load rating (C)	106 kN
Maximum Capacity / Filling Slot	No