



Bearing No. H414249/H414210

e	0.36
d	71,438 mm
D	136,525 mm
T	41,275 mm
B	41,275 mm
C	31,75 mm
a	30,6 mm
Da	121 mm
B_	41.275
Db	129 mm
da	89 mm
Y0	0.92
db	83 mm
C0	297
D_	136.525
Z_	17
C_	31.75
Y1	1.7
DE_	120.423
SLR	30
D_a	121
DI_	86.641
DA1	18.294
DA2	16.297
CUP	0.796
DA_	17.301
D_b	129
RAr	273.498
SDM_	103.662
KBRG	3161

yobi	H414249/H414210
CONE	1.83
ALP21	27
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	50
r min.	3,5 mm
LangID	1
Weight	2,626 Kg
ALPHA_	13.483
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	3600
outer r	3.3
hidYobi	H414249/H414210
GRS rpm	2600
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	71.438x136.525x41.275
SHOG_yobi	H414249/H414210
Prod_Type3	TRBSR_ID_A
Width (mm)	41,275
Bearing number	H414249/H414210
Bore Diameter (mm)	71,438
Outer Diameter (mm)	136,525
Calculation factor (e)	0,36

(Oil) Lubrication Speed	3600 r/min
Calculation factor (Y0)	0,92
(Grease) Lubrication Speed	2600 r/min
Basic static load rating (C0)	297 kN
Basic dynamic load rating (C)	229 kN