




Bearing No. 7013CDB

D	100 mm
a	0.5 mm
C	18 mm
B	18 mm
d	65 mm
r1	0.6 mm
2B	36 mm
Width	18 mm
r min.	1.1 mm
Weight	0.470 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	71 mm
Da max.	96 mm
ra (max)	1 mm
da1 (min)	71 mm
Bore Size	65 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	65x100x18
da2 (min)	71 mm
Da2 (max)	96 mm
Da1 (max)	94 mm
Width (mm)	18
Configuration	Duplex
Bearing number	7013CDB
Angle (?)	15 °
Outside Diameter	100 mm
Static Load Rating	69,000 N

Bore Diameter (mm)	65
Dynamic Load Rating	60,500 N
Outer Diameter (mm)	100
Limiting Speed - Oil	10,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	7,800 rpm
(Grease) Lubrication Speed	7800 r/min
Basic dynamic load rating (C)	60,5 kN
Basic static load rating (C0)	69 kN