



Bearing No. 6026DDU

r	2
d	130 mm
D	200 mm
B	33 mm
C	33 mm
D_	200
C0	101
Z_	15
ra	2
fo	15.8
B_	33
DI_	144.362
SRI	10.68
SRE	10.68
DE_	185.638
DA_	20.638
D_a	191
KBRG	6161
SBRG	10
SRIN	-0.04
bomp	0
SREX	0.04
yobi	6026DDU
SRIX	0.04
Bore	5.118 Inch   130 Millimeter
SDM_	165
SREN	-0.04
mass	3.26
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	139
ALPHA_	0
r min.	2 mm
Weight	3,26 Kg
C_conv	106000
da max	148,5 mm
Da max.	191 mm
ra max.	2 mm
GRS rpm	1900
da min.	139 mm
hidYobi	6026DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	130x200x33
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	33
Prod_Type3	DGBB_SR_DD
Weight / LBS	7.1883
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6026DDU
Keyword String	Ball
Other Features	Deep Groove   Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch   0 Millimeter

Outer Race Width	1.299 Inch   33 Millimeter
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Outside Diameter	7.874 Inch   200 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	3.15
Internal Clearance	C0-Medium
Bore Diameter (mm)	130
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6026DDU
Internal Special Features	No
(Grease) Lubrication Speed	1 900 r/min
Basic static load rating (C0)	101 kN
Basic dynamic load rating (C)	106 kN
Maximum Capacity / Filling Slot	No