



**Bearing No. 6026N**

D	200 mm
d	130 mm
B	33 mm
C	33 mm
a	5.69 mm
b	3.5 mm
r1	0.5 mm
D1	193.65 mm
Width	33 mm
Weight	3.60 Kg
r min.	2 mm
r1 min.	0.5 mm
a (max)	5.7 mm
da (min)	138 mm
Cy (max)	8.4 mm
Da (max)	192 mm
Dx (min)	215 mm
ra (max)	2 mm
Factor fo	15.7
Bore Type	Cylindrical Bore
Enclosure	Open
Size (mm)	130x200x33
Bore Size	130 mm
Width (mm)	33
Groove Width	3.5 mm
Configuration	Single Row
Bearing number	6026N
Groove Diameter	193.7 mm
Outside Diameter	200 mm
Radial Clearance	0.018 to 0.048 mm

Static Load Rating	101,000 N
Bore Diameter (mm)	130
Dynamic Load Rating	106,000 N
Outer Diameter (mm)	200
Limiting Speed - Oil	3,800 rpm
Fillet Radius/Chamfer	2 mm
Limiting Speed - Grease	3,200 rpm
(Grease) Lubrication Speed	3200 r/min
Basic static load rating (C0)	101 kN
Basic dynamic load rating (C)	106 kN