



Bearing No. 6026N

a	5,69 mm
r	2
d	130 mm
D	200 mm
B	33 mm
C	33 mm
b	3,5 mm
fo	15.8
B_	33
ra	2
C0	101
D1	193,65 mm
D_	200
Z_	15
rn	0,5 mm
ro	0.6
DE_	185.638
SRI	10.68
D_a	191
DA_	20.638
SRE	10.68
DI_	144.362
yobi	6026N
mass	3.26
SBRG	10
bomp	0
KBRG	6101
SREX	0.04
SREN	-0.04
SRIN	-0.04

SDM_	165
SRIX	0.04
ALPHA_	0
r min.	2 mm
C_conv	106000
da max	148,5 mm
da min	139
Weight	3,26 Kg
LangID	1
ra max.	2 mm
Da max.	191 mm
Oil rpm	3600
da min.	139 mm
r0 max.	0,6 mm
hidYobi	6026N
GRS rpm	3000
hidTable	ecat_NSRDGB
Size (mm)	130x200x33
Prod_Type3	DGBB_SR_N_OT
Width (mm)	33
Bearing number	6026N
Bore Diameter (mm)	130
Outer Diameter (mm)	200
(Oil) Lubrication Speed	3 600 r/min
(Grease) Lubrication Speed	3 000 r/min
Basic dynamic load rating (C)	106 kN
Basic static load rating (C0)	101 kN