



Bearing No. 6026Z

D	200,000 mm
d	130,000 mm
B	33,000 mm
C	33,000 mm
Noun	Bearing
Bore	5.118 Inch 130 Millimeter
UNSPSC	31171504
series:	60
Category	Single Row Ball Bearing
Size (mm)	130x200x33
Enclosure	1 Metal Shield
Inventory	0.0
Snap Ring	No
Width (mm)	33,000
bore type:	Round
Weight / LBS	6.97
maximum rpm:	3800 RPM
Product Group	B00308
closure type:	Single Shield
Inch - Metric	Metric
Cage Material	Steel
Keyword String	Ball
bore diameter:	130 mm
Bearing number	6026Z
overall width:	33 mm
cage material:	Steel
fillet radius:	2 mm
finish/coating:	Uncoated
Rolling Element	Ball Bearing

Precision Class	ABEC 1 ISO P0
Outer Race Width	1.299 Inch 33 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
precision rating:	ISO Class 0
outside diameter:	200 mm
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	3.16
inner ring width:	33 mm
outer ring width:	33 mm
Manufacturer Name	NTN
Internal Clearance	C0-Medium
Bore Diameter (mm)	130,000
maximum rpm (oil):	3800 rpm
internal clearance:	CN
Outer Diameter (mm)	200,000
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
static load capacity:	101000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3200 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	106000 N

Manufacturer Item Number	6026Z
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No