



Bearing No. 6026ZNR

a	5.69 mm
f	3.1 mm
b	3.5 mm
d	130 mm
D	200 mm
B	33 mm
C	33 mm
r1	0.5 mm
D2	212.9 mm
D1	193.65 mm
Width	33 mm
Weight	3.60 Kg
r min.	2 mm
b (min)	3.5 mm
r1 min.	0.5 mm
a (max)	5.7 mm
Cy (max)	8.4 mm
D1 (max)	193.7 mm
ra (max)	2 mm
Da (max)	192 mm
da (min)	138 mm
Dx (min)	215 mm
Factor fo	15.7
Bore Size	130 mm
Size (mm)	130x200x33
Bore Type	Cylindrical Bore
Enclosure	Single Shield with Snap Ring
Width (mm)	33
Configuration	Single Row

Bearing number	6026ZNR
Snap Ring Width	3.1 mm
Outside Diameter	200 mm
Radial Clearance	0.018 to 0.048 mm
Static Load Rating	101,000 N
Bore Diameter (mm)	130
Dynamic Load Rating	106,000 N
Outer Diameter (mm)	200
Limiting Speed - Oil	3,800 rpm
Fillet Radius/Chamfer	2 mm
Limiting Speed - Grease	3,200 rpm
Snap Ring Outside Diameter	212.9 mm
(Grease) Lubrication Speed	3200 r/min
Basic static load rating (C0)	101 kN
Basic dynamic load rating (C)	106 kN