



Bearing No. 6026ZZ

D	200 mm
d	130 mm
B	33 mm
C	33 mm
Noun	Bearing
Bore	5.118 Inch 130 Millimeter
Width	33 mm
UNSPSC	31171504
r min.	2 mm
Weight	3.92 Kg
da min.	138 mm
Da max.	192 mm
ra max.	2.0 mm
Category	Single Row Ball Bearing
ra (max)	2 mm
Da (max)	192 mm
da (min)	138 mm
Factor fo	15.7
Inventory	0.0
Bore Size	130 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	130x200x33
Width (mm)	33
Configuration	Single Row
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric

Other Features	Deep Groove
Keyword String	Ball
Bearing number	6026ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.nachiamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
Outer Race Width	1.299 Inch 33 Millimeter
Radial Clearance	0.018 to 0.048 mm
Weight / Kilogram	0
Manufacturer Name	NACHI
Bore Diameter (mm)	130
Internal Clearance	C0-Medium
Static Load Rating	101,000 N
Dynamic Load Rating	106,000 N
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	2 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	3,200 rpm
Internal Special Features	No

Basic dynamic load rating (C)	106 kN
Basic static load rating (C0)	101 kN
Maximum Capacity / Filling Slot	No