



Bearing No. 6026ZZ

D	200 mm
d	130 mm
B	33 mm
C	33 mm
r	2
Z_	15
B_	33
D_	200
ra	2
C0	101
fo	15.8
DI_	144.362
SRI	10.68
D_a	191
DE_	185.638
DA_	20.638
SRE	10.68
SRIN	-0.04
SBRG	10
yobi	6026ZZ
SDM_	165
SREX	0.04
KBRG	6141
bomp	0
mass	3.26
SRIX	0.04
Bore	5.118 Inch 130 Millimeter
SREN	-0.04
Noun	Bearing

ALPHA_	0
da min	139
LangID	1
r min.	2 mm
UNSPSC	31171504
da max	148,5 mm
C_conv	106000
Weight	3,26 Kg
ra max.	2 mm
hidYobi	6026ZZ
GRS rpm	3000
Da max.	191 mm
da min.	139 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	130x200x33
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	33
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	7.1883
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6026ZZ
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	7.874 Inch 200 Millimeter
Inner Race Width	0 Inch 0 Millimeter

Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.299 Inch 33 Millimeter
Weight / Kilogram	3.2
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	130
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	3 000 r/min
Basic static load rating (C0)	101 kN
Basic dynamic load rating (C)	106 kN
Maximum Capacity / Filling Slot	No