



Bearing No. 6026ZZ

D	200 mm
d	130 mm
B	33 mm
C	33 mm
rn	0,5 mm
Noun	Bearing
Bore	5.118 Inch 130 Millimeter
UNSPSC	31171504
da max	148 mm
Weight	3,16 Kg
r min.	2 mm
da min.	139 mm
Da max.	191 mm
ra max.	2 mm
series:	60
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	130x200x33
Inventory	0.0
Snap Ring	No
Width (mm)	33
bore type:	Round
Weight / LBS	7.20911
maximum rpm:	3800 RPM
closure type:	Double Shielded
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6026ZZ
overall width:	33 mm
bore diameter:	130 mm
cage material:	Steel
fillet radius:	2 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.299 Inch 33 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	33 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	33 mm
outside diameter:	200 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	130
Outer Diameter (mm)	200
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3200 rpm
static load capacity:	101000 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	106000 N
Internal Special Features	No
(Grease) Lubrication Speed	3 200 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	101 kN
Basic dynamic load rating (C)	106 kN
Maximum Capacity / Filling Slot	No