



Bearing No. 32022JR

e	0.43
d	110 mm
D	170 mm
T	38 mm
B	38 mm
C	29 mm
a	36,1 mm
Y0	0.77
Y1	1.39
Db	163 mm
Cu	56.7
Cr	312
C0r	395
Noun	Bearing
Bore	4.331 Inch 110 Millimeter
a(mm)	36.1
da max	122 mm
Da min	152 mm
UNSPSC	31171516
r min.	2,5 mm
Weight	3,12 Kg
r(min)	2.5
Db(min)	163
r1(min)	2
da(min)	122
db(max)	122
Da(max)	160
Da(min)	152
ra(max)	2

Sa(min)	7
r1 min.	2 mm
da min.	122 mm
Da max.	160 mm
db max.	122 mm
Db min.	163 mm
ra max.	2 mm
r2 min.	2 mm
rb(max)	2
rb max.	2 mm
Sb(min)	9
Category	Tapered Roller Bearings Assembly
Oil lub.	2800
Component	Assembly
Inventory	0.0
Size (mm)	110x170x38
Width (mm)	38
Grease lub.	2100
Bearing No.	32022JR
Basic Number	32022
Weight / LBS	6.878
Product Group	B04334
Inch - Metric	Metric
Bearing number	32022JR
Assembly Width	1.496 Inch 38 Millimeter
Other Features	High Load Capacity
Keyword String	Tapered
Precision Class	Standard
Long Description	Assembly; Standard Precision; 110MM Bore; 170MM Outside Diameter; 38MM

	Assembly Width; Single Row of Rollers
Outside Diameter	6.693 Inch 170 Millimeter
(Refer.)Mass(kg)	3.12
Manufacturer URL	http://www.koyousa.com
Manufacturer Name	KOYO
Weight / Kilogram	3.37
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.20.00.00
Number of Tapered Rows	Single Row
Calculation factor (e)	0,43
Flange Outside Diameter	0 Inch 0 Millimeter
Calculation factor (Y0)	0,77
(Oil) Lubrication Speed	2800 r/min
Manufacturer Item Number	32022JR
(Grease) Lubrication Speed	2100 r/min
Basic static load rating (C0)	395 kN
Basic dynamic load rating (C)	248 kN