



### Bearing No. 2315SK

e	0.38
d	75 mm
D	160 mm
B	55 mm
C	55 mm
Y0	1.7
Y2	2.5
Y1	1.6
Mass	4.77 kg
ra max	2 mm
Da max	149 mm
Ce min	5 mm
db min	82 mm
da max	96 mm
da min	86 mm
rs min	2.1 mm
Weight	4,77 Kg
r min.	2,1 mm
Da max.	149 mm
da min.	86 mm
ra max.	2 mm
Size (mm)	75x160x55
Width (mm)	55
Nlim (oil)	4,300 rpm
Nlim (grease)	3,400 rpm
Bearing number	2315SK
Precision class	P0
Dynamic load, C	125 kN
Static load, C0	43 kN
Bore Diameter (mm)	75

Outer Diameter (mm)	160
Radial clearance class	CN
Calculation factor (e)	0,38
(Oil) Lubrication Speed	4 300 r/min
Calculation factor (Y1)	1,6
Calculation factor (Y0)	1,7
(Grease) Lubrication Speed	3 400 r/min
Associated sleeve reference	H2315X
Basic dynamic load rating (C)	125 kN
Basic static load rating (C0)	43 kN
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C