



Bearing No. 7014CDB

| | |
|--------------------|------------------|
| D | 110 mm |
| a | 0.4 mm |
| C | 20 mm |
| B | 20 mm |
| d | 70 mm |
| r1 | 0.6 mm |
| 2B | 40 mm |
| Width | 20 mm |
| r min. | 1.1 mm |
| Weight | 0.660 Kg |
| ra max. | 0.6 mm |
| r1 min. | 0.6 mm |
| da min. | 76 mm |
| Da max. | 106 mm |
| ra (max) | 1 mm |
| da1 (min) | 76 mm |
| Bore Size | 70 mm |
| Enclosure | Open |
| Bore Type | Cylindrical Bore |
| ra1 (max) | 0.6 mm |
| Size (mm) | 70x110x20 |
| da2 (min) | 76 mm |
| Da2 (max) | 106 mm |
| Da1 (max) | 104 mm |
| Width (mm) | 20 |
| Configuration | Duplex |
| Bearing number | 7014CDB |
| Angle (?) | 15 ° |
| Outside Diameter | 110 mm |
| Static Load Rating | 86,500 N |

| | |
|-------------------------------|------------|
| Bore Diameter (mm) | 70 |
| Dynamic Load Rating | 76,500 N |
| Outer Diameter (mm) | 110 |
| Limiting Speed - Oil | 9,600 rpm |
| Fillet Radius/Chamfer | 1.1 mm |
| Limiting Speed - Grease | 7,100 rpm |
| (Grease) Lubrication Speed | 7100 r/min |
| Basic dynamic load rating (C) | 76,5 kN |
| Basic static load rating (C0) | 86,5 kN |