



Bearing No. 7014CDB/GNP4

C	40 mm
d	70 mm
B	40 mm
D	110 mm
Noun	Bearing
Bore	2.756 Inch 70 Millimeter
Width	1.575 Inch 40 Millimeter
UNSPSC	31171531
Preload	Light
Category	Precision Ball Bearings
Size (mm)	70x110x40
Inventory	0.0
Enclosure	Open
Width (mm)	40
duplex type:	Back to Back
Flush Ground	Yes
Weight / LBS	2.59
Inch - Metric	Metric
Cage Material	Nylon
Raceway Style	1 Rib Outer Ring
Product Group	B04270
closure type:	Open
Contact Angle	15 Degree
bore diameter:	70 mm
cage material:	Nylon
overall width:	40 mm
Keyword String	Angular Contact Ball
contact angle:	15 °
fillet radius:	1.1 mm

Bearing number	7014CDB/GNP4
Other Features	Single Row Angular Contact
Precision Class	ABEC 7 ISO P4
finish/coating:	Uncoated
Angle (?)	15 °
Rolling Element	Ball Bearing
Material - Ball	Steel
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	4.331 Inch 110 Millimeter
Long Description	70MM Bore; 110MM Outside Diameter; 40MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 15 Degree Contact Angle; Nylon Cage Material; 1 Rib Outer Ring Racew
Manufacturer Name	NTN
inner ring width:	20 mm
precision rating:	ISO Class 4
outside diameter:	110 mm
Weight / Kilogram	1.18
bearing material:	High Carbon Chrome Steel
outer ring width:	20 mm
Number of Bearings	2 (1 Pair)
Bore Diameter (mm)	70
maximum rpm (oil):	16640 rpm
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Mounting Arrangement	Duplex-Back to Back

maximum rpm (grease):	10400 rpm
Harmonized Tariff Code	8482.10.50.28
Manufacturer Item Number	7014CDB/GNP4
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C