



Bearing No. 7014CDF

D	110 mm
a	0.4 mm
C	20 mm
B	20 mm
d	70 mm
r1	0.6 mm
2B	40 mm
Width	20 mm
r min.	1.1 mm
Weight	0.660 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	76 mm
Da max.	106 mm
ra (max)	1 mm
da1 (min)	76 mm
Bore Size	70 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	70x110x20
da2 (min)	76 mm
Da2 (max)	106 mm
Da1 (max)	104 mm
Width (mm)	20
Configuration	Duplex
Bearing number	7014CDF
Angle (?)	15 °
Outside Diameter	110 mm
Static Load Rating	86,500 N

Bore Diameter (mm)	70
Dynamic Load Rating	76,500 N
Outer Diameter (mm)	110
Limiting Speed - Oil	9,600 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	7,100 rpm
(Grease) Lubrication Speed	7100 r/min
Basic dynamic load rating (C)	76,5 kN
Basic static load rating (C0)	86,5 kN