



Bearing No. NU411

|            |           |
|------------|-----------|
| C          | 33 mm     |
| d          | 55 mm     |
| D          | 140 mm    |
| B          | 33 mm     |
| B2         | -         |
| Cu         | 19.6      |
| Ew         | -         |
| d1         | -         |
| B1         | -         |
| Cr         | 174       |
| Fw         | 77.2 mm   |
| C0r        | 138       |
| r min.     | 2.1 mm    |
| Weight     | 2.51 Kg   |
| r(min)     | 2.1       |
| da(min)    | -         |
| db(min)    | 66        |
| db(max)    | 76        |
| dc(min)    | -         |
| r1(min)    | 2.1       |
| dd(min)    | -         |
| Da(max)    | 129       |
| Db(max)    | -         |
| Db(min)    | -         |
| r1 min.    | 2.1 mm    |
| ra(max)    | 2         |
| rb(max)    | 2         |
| Oil lub.   | 6100      |
| Size (mm)  | 55x140x33 |
| Width (mm) | 33        |
|            |           |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 4600       |
| Bearing No.                   | NU411      |
| Bearing number                | NU411      |
| (Refer.)Mass(kg)              | 2.51       |
| Bore Diameter (mm)            | 55         |
| Outer Diameter (mm)           | 140        |
| (Grease) Lubrication Speed    | 4600 r/min |
| Basic static load rating (C0) | 138 kN     |
| Basic dynamic load rating (C) | 142 kN     |