



**Bearing No. 32026-X-N11CA-A200-250**

|                     |                                         |
|---------------------|-----------------------------------------|
| m                   | 10,3 kg / Weight                        |
| D                   | 200 mm                                  |
| e                   | 0,43                                    |
| A                   | 22 mm                                   |
| d                   | 130 mm                                  |
| 2T                  | 90 mm                                   |
| 2B                  | 90 mm                                   |
| Size (mm)           | 130x200x90                              |
| Width (mm)          | 90                                      |
| C <sub>r</sub>      | 560000 N / Dynamic load rating (radial) |
| Y <sub>2</sub>      | 2,31                                    |
| Y <sub>1</sub>      | 1,55                                    |
| Y <sub>0</sub>      | 1,52                                    |
| n <sub>G</sub>      | 3100 1/min                              |
| n <sub>B</sub>      | 1870 1/min / Reference speed            |
| C <sub>ur</sub>     | 122000 N / Fatigue limit load, radial   |
| C <sub>0r</sub>     | 1100000 N / Static load rating (radial) |
| Bearing number      | 32026-X-N11CA-A200-250                  |
| r <sub>b max</sub>  | 2 mm                                    |
| D <sub>a min</sub>  | 178 mm                                  |
| D <sub>a max</sub>  | 190 mm                                  |
| C <sub>a min</sub>  | 8 mm                                    |
| d <sub>a max</sub>  | 144 mm                                  |
| Bore Diameter (mm)  | 130                                     |
| Outer Diameter (mm) | 200                                     |

|                        |      |
|------------------------|------|
| r <sub>3</sub> , 4 min | 2 mm |
|------------------------|------|