



Bearing No. 6030DDU

r	2.1
d	150 mm
D	225 mm
B	35 mm
C	35 mm
D_	225
C0	126
Z_	16
ra	2
fo	15.9
B_	35
DI_	165.275
SRI	11.5
SRE	11.5
DE_	209.725
DA_	22.225
D_a	214
KBRG	6161
SBRG	10
SRIN	-0.04
bomp	0
SREX	0.04
yobi	6030DDU
SRIX	0.04
Bore	5.906 Inch 150 Millimeter
SDM_	187.5
SREN	-0.04
mass	4.24
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	161
ALPHA_	0
r min.	2,1 mm
Weight	4,24 Kg
C_conv	126000
da max	170 mm
Da max.	214 mm
ra max.	2 mm
GRS rpm	1700
da min.	161 mm
hidYobi	6030DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	150x225x35
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	35
Prod_Type3	DGBB_SR_DD
Weight / LBS	9.3492
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6030DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	8.858 Inch 225

	Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	150MM Bore; 225MM Outside Diameter; 35MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.378 Inch 35 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	4.5
Internal Clearance	C0-Medium
Bore Diameter (mm)	150
Outer Diameter (mm)	225
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6030DDU
Internal Special Features	No
(Grease) Lubrication Speed	1 700 r/min
Basic static load rating (C0)	126 kN
Basic dynamic load rating (C)	126 kN
Maximum Capacity / Filling Slot	No