



Bearing No. 7015DF

D	115 mm
a	17.4 mm
C	20 mm
B	20 mm
d	75 mm
r1	0.6 mm
2B	40 mm
Width	20 mm
r min.	1.1 mm
Weight	0.695 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	81 mm
Da max.	111 mm
ra (max)	1 mm
da1 (min)	81 mm
Bore Size	75 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	75x115x20
da2 (min)	81 mm
Da2 (max)	111 mm
Da1 (max)	109 mm
Width (mm)	20
Configuration	Duplex
Bearing number	7015DF
Angle (?)	30 °
Outside Diameter	115 mm
Static Load Rating	83,000 N

Bore Diameter (mm)	75
Dynamic Load Rating	70,500 N
Outer Diameter (mm)	115
Limiting Speed - Oil	5,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	3,800 rpm
(Grease) Lubrication Speed	3800 r/min
Basic dynamic load rating (C)	70,5 kN
Basic static load rating (C0)	83 kN