



Bearing No. 32034JR

C	43 mm
d	170 mm
D	260 mm
T	57 mm
B	57 mm
a	55,8 mm
e	0.44
Cr	661
Y0	0.74
Y1	1.35
Cu	105
Db	249 mm
C0r	905
Bore	6.693 Inch 170 Millimeter
Noun	Bearing
a(mm)	55.8
r(min)	3
UNSPSC	31171516
Weight	10,5 Kg
r min.	3 mm
Da min	230 mm
da max	187 mm
Db min.	249 mm
ra max.	2,5 mm
r1 min.	2,5 mm
r1(min)	2.5
r2 min.	2,5 mm
da(min)	184
da min.	184 mm

db(max)	187
Da(max)	248
Da(min)	230
Db(min)	249
Sa(min)	10
Sb(min)	14
rb(max)	2
Da max.	248 mm
db max.	187 mm
rb max.	2 mm
ra(max)	2.5
Category	Tapered Roller Bearings Assembly
Oil lub.	1700
Inventory	0.0
Component	Assembly
Size (mm)	170x260x57
Width (mm)	57
Bearing No.	32034JR
Grease lub.	1300
Weight / LBS	23.149
Basic Number	32034
Inch - Metric	Metric
Product Group	B04334
Bearing number	32034JR
Assembly Width	2.244 Inch 57 Millimeter
Keyword String	Tapered
Other Features	High Load Capacity
Precision Class	Standard
(Refer.)Mass(kg)	10.5
Manufacturer URL	http://www.koyousa.com
Outside Diameter	10.236 Inch 260

	Millimeter
Long Description	Assembly; Standard Precision; 170MM Bore; 260MM Outside Diameter; 57MM Assembly Width; Single Row of Rollers
Manufacturer Name	KOYO
Weight / Kilogram	11.298
Bore Diameter (mm)	170
Outer Diameter (mm)	260
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,44
Calculation factor (Y0)	0,74
(Oil) Lubrication Speed	1700 r/min
Flange Outside Diameter	0 Inch 0 Millimeter
Manufacturer Item Number	32034JR
(Grease) Lubrication Speed	1300 r/min
Basic static load rating (C0)	905 kN
Basic dynamic load rating (C)	526 kN