



Bearing No. 32034X

| | |
|------------------------|------------|
| D | 260 mm |
| d | 170 mm |
| T | 57 mm |
| B | 57 mm |
| C | 43 mm |
| a | 56 mm |
| d1 | 214 mm |
| Weight | 10,5 Kg |
| db min | 182 mm |
| Da min | 230 mm |
| da max | 187 mm |
| Ca min. | 10 mm |
| Cb min. | 14 mm |
| Db min. | 249 mm |
| Da max. | 248 mm |
| r1 min. | 3 mm |
| r4 min. | 2,5 mm |
| r3 min. | 2,5 mm |
| r2 min. | 3 mm |
| rb max. | 2,5 mm |
| ra max. | 3 mm |
| Size (mm) | 170x260x57 |
| Width (mm) | 57 |
| Limiting speed | 2200 r/min |
| Bearing number | 32034X |
| Reference speed | 1700 r/min |
| Bore Diameter (mm) | 170 |
| Outer Diameter (mm) | 260 |
| Calculation factor (e) | 0,44 |
| Calculation factor (Y) | 1,35 |
| | |

| | |
|-------------------------------|--------|
| Fatigue load limit (Pu) | 88 |
| Basic dynamic load rating (C) | 512 kN |
| Basic static load rating (C0) | 915 kN |