




Bearing No. 7016 ACB/P4A

D	125 mm
d	80 mm
B	22 mm
a	35.1 mm
Ball - z	27
Size (mm)	80x125x22
Width (mm)	22
Mass bearing	0.92 kg
d_n	98 mm
d_n	98 mm
D_2	111.4 mm
d_1	96.7 mm
d_2	94.3 mm
D_2	111.4 mm
d_2	94.3 mm
d_1	96.7 mm
Bearing number	7016 ACB/P4A
Preload class A	144 N/micron
G_{ref}	10.49 cm ³
Preload class C	276 N/micron
Preload class B	182 N/micron
Number of balls z	27
Bore Diameter (mm)	80
r_b max.	0.6 mm
r_a max.	1 mm
D_b max.	121.8 mm
D_a max.	119 mm
d_a min.	86 mm
d_b min.	86 mm

Outer Diameter (mm)	125
D_b - max.	121.8 mm
d_a - min.	86 mm
Calculation factor e	0.68
Calculation factor f	1.07
r_b - max.	0.6 mm
D_a - max.	119 mm
r_a - max.	1 mm
$r_{3,4}$ min.	0.6 mm
$r_{1,2}$ min.	1.1 mm
Ball - D_w	9.525 mm
d_b - min.	86 mm
$r_{1,2}$ - min.	1.1 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - e	0.68
Calculation factor - f	1.07
Basic dynamic load rating C	30.2 kN
Ball diameter D_w	9.525 mm
Preload class B G_B	300 N
Preload class C G_C	900 N
Basic dynamic load rating - C	25.1 kN
Preload class A G_A	150 N
Preload class B - G_B	300 N
Preload class C - G_C	900 N
Preload class A - G_A	150 N
Fatigue load limit P_u	0.9 kN
Calculation factor f_1	0.99
Calculation factor f_{2C}	1.04
Calculation factor f_{2A}	1
Calculation factor f_{HC}	1

Calculation factor f_{2B}	1.01
Limiting speed for oil lubrication	19000 mm/min
Fatigue load limit - P_u	0.9 kN
Calculation factor - f_1	0.99
Calculation factor - Y_2	1.41
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_0	0.76
Calculation factor - f_{HC}	1
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.04
Calculation factor - f_{2B}	1.01
Limiting speed for grease lubrication	12000 r/min
Basic static load rating C_0	32.5 kN
Static axial stiffness, preload class B	182 N/ μ m
Static axial stiffness, preload class A	144 N/ μ m
Attainable speed for grease lubrication	12000 r/min
Static axial stiffness, preload class C	276 N/ μ m
Basic static load rating - C_0	21.6 kN
Attainable speed for oil-air lubrication	19000 r/min
Reference grease quantity G_{ref}	10.49 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor	0.38

(single, tandem) Y_0	
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back- to-back, face-to-face) Y_1	0.92
Calculation factor (back- to-back, face-to-face) Y_2	1.41
Calculation factor (back- to-back, face-to-face) Y_0	0.76
Calculation factor (back- to-back, face-to-face) X_2	0.67