



Bearing No. NU336

C	75 mm
d	180 mm
D	380 mm
B	75 mm
Fw	232 mm
Noun	Bearing
Bore	7.087 Inch 180 Millimeter
Width	2.953 Inch 75 Millimeter
UNSPSC	31171547
Weight	44,2 Kg
r min.	4 mm
r1 min.	4 mm
Profile	Complete with Outer and Inner Ring
Retainer	Yes
flanges:	(2) Outer Ring
Category	Cylindrical Roller Bearing
Size (mm)	180x380x75
Snap Ring	No
Separable	Inner Ring - Both Sides
Inventory	0.0
Width (mm)	75
bore type:	Straight
maximum rpm:	2000 rpm
Weight / LBS	93.483
Bore Profile	Straight
Inch - Metric	Metric
Cage Material	Steel

Product Group	B04144
closure type:	Open
bore diameter:	180 mm
overall width:	75 mm
cage material:	High Strength, 2 piece, Machined Brass
fillet radius:	3 mm
Bearing number	NU336
Relubricatable	Yes
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage On Outer Ring ID
Precision Class	RBEC 1 ISO P0
Rolling Element	Cylindrical Roller Bearing
finish/coating:	Uncoated
number of rows:	1
Outside Diameter	14.961 Inch 380 Millimeter
Long Description	180MM Bore; Straight Bore Profile; 380MM Outside Diameter; 75MM Width; Steel Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
ring separation:	Separable Inner Ring
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	42.44
outside diameter:	380 mm
precision rating:	ISO Class 0
Manufacturer Name	NTN
bearing material:	Hardened Alloy Steel

Internal Clearance	C0-Medium
Bore Diameter (mm)	180
Outer Diameter (mm)	380
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	1150000 N
Harmonized Tariff Code	8482.50.00.00
dynamic load capacity:	905000 N
Manufacturer Item Number	NU336
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	1 700 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	905 kN
Basic static load rating (C0)	1 150 kN