



Bearing No. 7017 ACE/P4AL1

b	1.8 mm
d	85 mm
a	36.3 mm
B	22 mm
D	130 mm
Ball - z	26
Size (mm)	130x85x22
Width (mm)	22
Mass bearing	0.9 kg
d <sub>2</sub>	98 mm
D <sub>1</sub>	114.12 mm
d <sub>n</sub>	103.5 mm
C <sub>1</sub>	6.5 mm
C <sub>2</sub>	3.8 mm
C <sub>3</sub>	3.8 mm
C <sub>2</sub>	3.8 mm
C <sub>1</sub>	6.5 mm
d <sub>n</sub>	103.5 mm
D <sub>1</sub>	114.12 mm
d <sub>2</sub>	98 mm
d <sub>1</sub>	100.83 mm
d <sub>1</sub>	100.83 mm
C <sub>3</sub>	3.8 mm
Bearing number	7017 ACE/P4AL1
Preload class A	186 N/micron
Preload class B	281 N/micron
G <sub>ref</sub>	12 cm <sup>3</sup>
Preload class C	369 N/micron
Number of balls z	26

Bore Diameter (mm)	130
$r_b$ max.	0.6 mm
$r_a$ max.	1 mm
$D_b$ max.	125.8 mm
$D_a$ max.	124 mm
$d_a$ min.	91 mm
$d_b$ min.	91 mm
Outer Diameter (mm)	85
$r_b$ - max.	0.6 mm
$r_{3,4}$ min.	0.6 mm
$d_b$ - min.	91 mm
$D_a$ - max.	124 mm
$D_b$ - max.	125.8 mm
$r_{1,2}$ min.	1.1 mm
$d_a$ - min.	91 mm
$r_a$ - max.	1 mm
Ball - $D_w$	11.112 mm
Calculation factor f	1.11
Calculation factor e	0.68
$r_{3,4}$ - min.	0.6 mm
Calculation factor - f	1.11
$r_{1,2}$ - min.	1.1 mm
Calculation factor - e	0.68
Ball diameter $D_w$	11.112 mm
Basic dynamic load rating C	32.5 kN
Preload class C $G_C$	1780 N
Basic dynamic load rating - C	32.5 kN
Preload class B $G_B$	890 N
Preload class A $G_A$	290 N
Preload class C - $G_C$	1780 N

Preload class A - $G_A$	290 N
Preload class B - $G_B$	890 N
Calculation factor $f_1$	0.99
Fatigue load limit $P_u$	1.14 kN
Calculation factor $f_{HC}$	1
Calculation factor $f_{2C}$	1.06
Calculation factor $f_{2B}$	1.03
Calculation factor $f_{2A}$	1
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Limiting speed for oil lubrication	20000 mm/min
Calculation factor - $Y_1$	0.92
Fatigue load limit - $P_u$	1.1 kN
Calculation factor - $f_1$	0.99
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{HC}$	1
Calculation factor - $f_{2C}$	1.06
Calculation factor - $f_{2B}$	1.03
Limiting speed for grease lubrication	13000 r/min
Basic static load rating $C_0$	28 kN
Static axial stiffness, preload class A	186 N/ $\mu$ m
Static axial stiffness, preload class C	369 N/ $\mu$ m
Static axial stiffness, preload class B	281 N/ $\mu$ m
Attainable speed for grease lubrication	13000 r/min

Basic static load rating - $C_0$	28 kN
Attainable speed for oil-air lubrication	20000 r/min
Reference grease quantity $G_{ref}$	12 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67