



Bearing No. EE763330/763410

|                                  |                     |
|----------------------------------|---------------------|
| C                                | 66,675 mm           |
| r                                | 6,3 mm              |
| d                                | 838,2 mm            |
| D                                | 1041,4 mm           |
| T                                | 93,662 mm           |
| B                                | 88,9 mm             |
| a                                | 83,1 mm             |
| R                                | 6,3 mm              |
| Db                               | 996,0 mm            |
| da                               | 870 mm              |
| db                               | 876 mm              |
| Da                               | 1001,0 mm           |
| Weight                           | 154,58 Kg           |
| Size (mm)                        | 838.2x1041.4x93.662 |
| Width (mm)                       | 93,662              |
| Factor (K)                       | 1,33                |
| Factor (G1)                      | 14677,1             |
| Factor (Cg)                      | 0,1228              |
| Factor (G2)                      | 1745,2              |
| Bearing number                   | EE763330/763410     |
| Bore Diameter (mm)               | 838,2               |
| Outer Diameter (mm)              | 1041,4              |
| Calculation factor (e)           | 0,44                |
| Basic static load rating (C0)    | 5930 kN             |
| Basic dynamic load rating (C1)   | 2160 kN             |
| Basic dynamic load rating (C90)  | 561                 |
| Basic dynamic load rating (Ca90) | 420                 |

