



Bearing No. 7017CDT

D	130 mm
a	1.4 mm
C	22 mm
B	22 mm
d	85 mm
r1	0.6 mm
2B	44 mm
Width	22 mm
r min.	1.1 mm
Weight	0.960 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	91 mm
Da max.	126 mm
ra (max)	1 mm
da1 (min)	91 mm
Bore Size	85 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	85x130x22
da2 (min)	91 mm
Da2 (max)	126 mm
Da1 (max)	124 mm
Width (mm)	22
Configuration	Duplex
Bearing number	7017CDT
Angle (?)	15 °
Outside Diameter	130 mm
Static Load Rating	118,000 N

Bore Diameter (mm)	85
Dynamic Load Rating	98,500 N
Outer Diameter (mm)	130
Limiting Speed - Oil	8,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	5,900 rpm
(Grease) Lubrication Speed	5900 r/min
Basic dynamic load rating (C)	98,5 kN
Basic static load rating (C0)	118 kN