




Bearing No. 7018 CD/P4AL

b	2.2 mm
d	90 mm
a	27.5 mm
B	24 mm
D	140 mm
Ball - z	20
Size (mm)	140x90x24
Width (mm)	24
Mass bearing	1.16 kg
d ₂	105.4 mm
D ₁	124.6 mm
d _n	108.7 mm
C ₁	13.4 mm
C ₂	5.2 mm
C ₃	4.3 mm
C ₂	5.2 mm
C ₁	13.4 mm
d _n	108.7 mm
D ₁	124.6 mm
d ₂	105.4 mm
d ₁	105.4 mm
d ₁	105.4 mm
C ₃	4.3 mm
Bearing number	7018 CD/P4AL
Preload class B	141 N/micron
G _{ref}	15 cm3
Preload class C	198 N/micron
Preload class D	287 N/micron
Preload class A	103 N/micron

Number of balls z	20
d_a min.	97 mm
D_a max.	133 mm
d_b min.	97 mm
D_b max.	136 mm
r_a max.	1.5 mm
r_b max.	1 mm
Bore Diameter (mm)	140
Outer Diameter (mm)	90
$r_{1,2}$ min.	1.5 mm
d_a - min.	97 mm
d_b - min.	97 mm
D_a - max.	133 mm
Calculation factor f	1.14
r_b - max.	1 mm
$r_{3,4}$ min.	1 mm
D_b - max.	136 mm
Ball - D_w	15.875 mm
r_a - max.	1.5 mm
Calculation factor - f	1.14
$r_{3,4}$ - min.	1 mm
$r_{1,2}$ - min.	1.5 mm
Ball diameter D_w	15.875 mm
Basic dynamic load rating C	79.3 kN
Preload class B G_B	600 N
Preload class A G_A	300 N
Preload class D G_D	2400 N
Preload class C G_C	1200 N
Basic dynamic load rating - C	79.3 kN
Preload class B - G_B	600 N

Preload class C - G_C	1200 N
Preload class D - G_D	2400 N
Preload class A - G_A	300 N
Calculation factor f_1	1
Calculation factor f_0	15.6
Fatigue load limit P_u	3 kN
Calculation factor f_{HC}	1
Calculation factor f_{2D}	1.09
Calculation factor f_{2B}	1.02
Calculation factor f_{2A}	1
Calculation factor - f	1
Calculation factor f_{2C}	1.05
Fatigue load limit - P_u	3 kN
Limiting speed for oil lubrication	15000 mm/min
Calculation factor - f_0	15.6
Calculation factor - f_{HC}	1
Calculation factor - f_{2A}	1
Calculation factor - f_{2D}	1.09
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.05
Limiting speed for grease lubrication	9000 r/min
Basic static load rating C_0	76.5 kN
Static axial stiffness, preload class B	141 N/ μ m
Static axial stiffness, preload class A	103 N/ μ m
Static axial stiffness, preload class C	198 N/ μ m
Static axial stiffness,	287 N/ μ m

preload class D	
Attainable speed for grease lubrication	9000 r/min
Basic static load rating - C_0	76.5 kN
Attainable speed for oil-air lubrication	15000 r/min
Reference grease quantity G_{ref}	15 cm ³