



Bearing No. 32207JR

D	72 mm
d	35 mm
T	24,25 mm
B	23 mm
C	19 mm
a	18,2 mm
e	0.37
Cr	86.9
Cu	12.2
Y0	0.88
Y1	1.60
C0r	82.4
Bore	1.378 Inch 35 Millimeter
Noun	Bearing
a(mm)	18.2
Da min	61 mm
da max	43 mm
Weight	0,453 Kg
r min.	1,5 mm
r(min)	1.5
UNSPSC	31171516
Db(min)	67
db(max)	43
Da(max)	63.5
Da(min)	61
r1(min)	1.5
Sa(min)	3
Sb(min)	5
ra(max)	1.5

rb(max)	1.5
da(min)	43.5
ra max.	1,5 mm
Db min.	67 mm
Da max.	63,5 mm
da min.	43,5 mm
r2 min.	1,5 mm
rb max.	1,5 mm
Oil lub.	7500
Category	Tapered Roller Bearings Assembly
Size (mm)	35x72x24.25
Component	Assembly
Inventory	1.0
Width (mm)	24,25
Grease lub.	5600
Bearing No.	32207JR
Basic Number	32207
Weight / LBS	0.999
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	0.955 Inch 24.25 Millimeter
Bearing number	32207JR
Precision Class	Standard
(Refer.)Mass(kg)	0.453
Outside Diameter	2.835 Inch 72 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 35MM Bore; 72MM Outside

	Diameter; 24.25MM Assembly Width; Single Row of Rollers
Weight / Kilogram	0.45
Manufacturer Name	KOYO
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Calculation factor (e)	0,37
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	7500 r/min
Calculation factor (Y0)	0,88
Manufacturer Item Number	32207JR
(Grease) Lubrication Speed	5600 r/min
Basic static load rating (C0)	82,4 kN
Basic dynamic load rating (C)	69,6 kN